# verde

FE-VE-12-D0-1060-27-B-SP-8

## specifications

| | |
|---|---|
| **Mounting Type** | spike |
| **Accessory Type** | 800mm Extension Rod |
| **CCT** | 2700k |
| **System Wattage** | 12W |
| **Control** | non-dim |
| **Beam Angle** | 10Â° x 60Â° |
| **finish** | Black |

## Family Features

- system wattage: 6W, 12W, 18W, 30W or 42W
- luminaire output: 350lm up to 2500lm
- CCT: 2700K, 3000K, 4000K, RGBW
- optics: 3˚, 8˚, 18˚, 24˚, 38˚, 60˚, 10˚x60˚, 20˚x55˚
- control: non-dim, 1-10V, DALI, DMX
- operating voltage: 24V
- finish: black or grey, powdercoat finish
- accessories: surface mount, spike or pole mount

## Overview

The Verde family consists of surface, spike and pole mounted spots with a lockable tilt angle suitable for various external lighting applications. Verde encompasses a minimalist sleek design with robust construction including a superior powder coating finish, toughened extra clear flush glass lens and anti syphon valve to prevent condensation build up inside the luminaire.

Verde offers four housing sizes from 6 to 42W with a range of dimming and colour temperatures including RGBW, with optics as narrow as 3 degrees through to 60 degrees, including oval options. The IP65 rating combined with a low glare SMD chip array ensure visual comfort and suitability for even the most exposed outdoor areas.

A versatile external spotlight suitable for gardens, facades and general outdoor lighting.

**customer service**
+61 (03) 9790 8999
lighting@verbatim.com.au
verbatimlighting.com.au