verde

FE-VE-42-DMX-1060-30-G-SP-8

specifications

Type Of Product	exterior
Brand	Forlite
Mounting Type	spike
Accessory Type	800mm Extension Rod
Luminaire Output	300lm, 750lm, 1100lm, 2500lm
CCT	3000k
System Wattage	42W
Control	DMX
Beam Angle	10Â˚ x 60Â˚
chip type	COB, SMD
Optics	12x 3.5W, 3x 2W, 3x 4W, 4x 3.5W, 4x 3W, 6x 3.5W, 6x 3W
Body	die-cast aluminium with powder-coat finish
Size	100 x 60 x 669mm, 100 x 60 x 969mm, 100 x 60 x 1169mm, 100 x 65 x 152mm, 100 x 60 x 169mm, 100 x 60 x 469mm, 128 x
finish	Grey
IP Rating	IP65
CRI	90
Lifetime	50000 hrs
Warranty	five years

Family Features

- system wattage: 6W, 12W, 18W, 30W or 42W
- luminaire output: 350lm up to 2500lm
- CCT: 2700K, 3000K, 4000K, RGBW
- optics: 3˚, 8˚, 18˚, 24˚, 38˚, 60˚, 10˚x60˚, 20˚x55˚
- control: non-dim, 1-10V, DALI, DMX
- operating voltage: 24V
- finish: black or grey, powdercoat finish
- accessories: surface mount, spike or pole mount

Overview

The Verde family consists of surface, spike and pole mounted spots with a lockable tilt angle suitable for various external lighting applications. Verde encompasses a minimalist sleek design with robust construction including a superior powder coating finish, toughened extra clear flush glass lens and anti syphon valve to prevent condensation build up inside the luminaire.

Verde offers four housing sizes from 6 to 42W with a range of dimming and colour temperatures including RGBW, with optics as narrow as 3 degrees

verde

FE-VE-42-DMX-1060-30-G-SP-8

through to 60 degrees, including oval options. The IP65 rating combined with a low glare SMD chip array ensure visual comfort and suitability for even the most exposed outdoor areas.

A versatile external spotlight suitable for gardens, facades and general outdoor lighting.