NERI

Antares S

N-ANT-S-B3-04-2-T4C-N-S

OVERVIEW

Antares encompasses design, visual comfort, performance and energy savings in a single luminaire. With an optical technology that allows to reach extremely high performance, thanks to its adjustable inclination joint, maximum flexibility is guaranteed.

Made of cast aluminum, with an IP66 protection rating, the screen is made of transparent extra-clear glass, 4mm thick, IK08 mechanical resistance.

The optical system is composed of overlapping PMMA lenses with constant high light transmission features. The wide emission surface and the perimeter reflector increase the emission efficiency maintaining reduced glare values. Customised light distributions can be obtained thanks to the flexibility in composing the lenses.

Designed with a button-opening system that does not require any type of tool, Antares was conceived to facilitate product installation and maintenance activities.

SPECIFICATIONS

TYPE OF PRODUCT	EXTERIOR, STREETLIGHT
BRAND	NERI
SYSTEM WATTAGE	10W, 11W, 16W, 17W, 18W, 23W, 24W, 25W, 29W, 31W, 32W, 38W, 40W, 41W, 48W, 50W, 52W, 59W, 62W, 65W, 70W
CCT	2700K
LUMINAIRE OUTPUT	4500LM
BEAM ANGLE	TYPE IV-C
CRI	70
DIMMING	AMPDIM
LIFETIME	100000HRS L90-B10

+61 (03) 9790 8999
lighting@verbatim.com.au
verbatimlighting.com.au

information is subject to change prior notice. Images are for illustrative purposes only.

NERI

Antares S

N-ANT-S-B3-04-2-T4C-N-S

	IP66
IK RATING	IK08
DIMENSIONS (L X D)	340MM X 608MM X 260MM
FINISH	NERI GREY
ACCESSORIES	BACK-SPILL SHIELD

IP RATING

+61 (03) 9790 8999
lighting@verbatim.com.au
verbatimlighting.com.au

information is subject to change prior notice. Images are for illustrative purposes only.