

OVERVIEW

Antares encompasses design, visual comfort, performance and energy savings in a single luminaire. With an optical technology that allows to reach extremely high performance, thanks to its adjustable inclination joint, maximum flexibility is guaranteed.

Made of cast aluminum, with an IP66 protection rating, the screen is made of transparent extra-clear glass, 4mm thick, IK08 mechanical resistance.

The optical system is composed of overlapping PMMA lenses with constant high light transmission features. The wide emission surface and the perimeter reflector increase the emission efficiency maintaining reduced glare values. Customised light distributions can be obtained thanks to the flexibility in composing the lenses.

Designed with a button-opening system that does not require any type of tool, Antares was conceived to facilitate product installation and maintenance activities.



SPECIFICATIONS

TYPE OF PRODUCT	EXTERIOR
BRAND	NERI
SYSTEM WATTAGE	24W
CCT	3000K
LUMINAIRE OUTPUT	3500LM
BEAM ANGLE	TYPE II-D
CRI	70
DIMMING	
LIFETIME	100000HRS L90-B10
IP RATING	IP66
IK RATING	IK08
DIMENSIONS (L X D)	340MM X 608MM X 260MM
FINISH	RAL9006 LIGHT GREY
ACCESSORIES	BACK-SPILL SHIELD

NERI

Antares s

N-ANT-S-B2-05-3-T2D-G-S