


- 3-CCT (3000K/4000K/5700K) selectable
- Deep recessed diffuser to reduce glare
- Extra wide rim front ring design
- Switch on the back to select CCT
- 20W, 1900-2100lm
- Equipped with 2-pin Australia AS3112 plug, ready to plug-in
- Triac dimmable
- IC-4 insulation rated, can be covered by insulating material during insulation
- 90° beam angle
- Lifetime 40,000 hrs



Order Code 66327

## General Data

Lamp Socket	Integrated downlight
Design	Deep Recessed diffuser

## Geometric Data

Height (mm)	132.5mm (including LED driver)
Diameter (mm)	240mm
Weight (g)	TBC

## Electric Data



Wattage	20W
Voltage	220-240 V AC
Power Factor	≥0.9
Operating Frequency	50/60 Hz


## Photometric Data

Total Luminous Flux (lm)	1900-2100lm
90° cone Luminous Flux (lm)	N/A
CRI	≥80
CCT	3000K/4000K/5700K
Luminous Intensity (cd)	TBC (measured at 4000K)
Beam Angle (°)	90°
Lifetime	40,000 hrs

## Equivalent to (W)

Operating Temperature: -20° to 45°





### Order Code

66327

### Product Description

Verbatim LED recessed downlight (deep recessed) 20W  
CCT selectable 1900-2100lm with AU plug (205/240mm)

### Technical Packaging Details

Giftbox Barcode	6943760263275
Inner Carton Barcode	N/A
Outer Carton Barcode	26943760263279
Pack Dimensions (LxWxH)	250 mm x 250 mm x 143 mm
Pack Weight	TBC
Carton Qty (Shipping Unit)	12
Carton Dimensions (LxWxH)	515 mm x 515 mm x 450 mm
Cartons/Layer	4
Layers/Pallet	2
Units/Pallet	96