

silver XS



silver series



architectural lighting requires the right luminaire. Highlighting and accenting with multiple sources rather than just flooding an area with light. The silver XS has a subtle aperture to minimise visual impact, and with an adjustable specular aluminium reflector and a range of beam angles to create the perfect effect.

specifications

| | |
|------------------|---|
| system wattage | 7W |
| CCT | 2700K, 3000K, 3500K, 4000K |
| luminaire output | 505lm - 562lm |
| beam angles | 20°, 35°, 55° |
| CRI | 90 |
| Macadam | 3 SDCM |
| control | on/off, triac, 1-10V, DALI, Casambi |
| cutout | Ø46mm for 5-25mm ceiling thickness |
| lifetime | 50,000hrs |
| build | die-cast aluminium & specular aluminium reflector |
| IP rating | IP20 |
| warranty | 5 years |
| accessories | black or white trim honeycomb filter frosted diffuser |



product code

| | | | | | | | | | | | | | | | |
|---------------|-----|-------------------|-----------|----------|----|-----------|---------|------------|-----|-----------|-------|----------------|-------|----------|----------|
| FV | - | SXS | - | 7 | - | x | - | x | - | x | - | x | - | R | |
| product group | vue | group destination | silver XS | wattage | 7W | dimmable | non-dim | beam angle | 20° | cct | 2700K | fixture colour | white | mounting | recessed |
| FV | vue | SXS | silver XS | 7 | 7W | Do | non-dim | 20 | 20° | 27 | 2700K | W | white | R | recessed |
| | | | | | | D1 | 1-10V | 35 | 35° | 30 | 3000K | B | black | | |
| | | | | | | D2 | TRIAC | 55 | 55° | 35 | 3500K | | | | |
| | | | | | | DD | DALI | | | 40 | 4000K | | | | |
| | | | | | | CS | Casambi | | | | | | | | |



customer service
+61 (03) 9790 8999
verbatimlighting.com.au

