



# led lighting product catalogue

2023

---



## contents

---

smooth .....	3
vue micro .....	6
silver .....	7
quantum .....	13
kub .....	15
elpin .....	17
polo .....	18
slim pendant .....	20
float round .....	21
float square .....	22
ligne circular .....	23
teso .....	24
ligne micro .....	27
artere axis 16 .....	28
artere axis 23 .....	31
ario deep .....	34
ario gen 2 .....	35
hellion .....	36
hellion wall .....	37
cortile .....	40
mighty bollard .....	41
halo bollard .....	42

# smooth S

vue series




a dark-light effect can create a soft and warm environment, and a curved edge transitions from light to dark gently. the overall effect being to draw the eye to the lit area or object.

the smooth range of architectural luminaires aims to provide the designer with the tools to create the perfect environment to connect with the end user.

## specifications

system wattage:	4W, 6W, 8W
luminaire output:	380lm to 770lm
CCT:	2700K, 3000K, 4000K, 5000K
optics:	15°, 24°, 38°
CRI:	90
control:	non-dim, 1-10V, triac, DALI, Casambi
operating voltage:	240Vac
finish:	white & black
housing:	die-cast aluminium
diffuser:	glass lens
enclosure protection:	IP20
operating temp:	25°C
lifetime:	50,000hrs
warranty:	5 years
accessories:	honeycomb filter, clear lens, frosted diffuser



## product code

product group	group designation	wattage	dimming	optics	cct	fixture colour	mounting	accessories
<b>FV</b> vue	<b>SMS</b> smooth S	<b>4</b> 4W	<b>X</b>	<b>X</b>	<b>X</b>	<b>X</b>	<b>R</b>	<b>X</b>
		<b>6</b> 6W	<b>D0</b> non-dim	<b>15</b> 15°	<b>27</b> 2700K	<b>B</b> black	<b>R</b> recessed	<b>H</b> honeycomb filter
		<b>8</b> 8W	<b>D1</b> 1-10V	<b>24</b> 24°	<b>30</b> 3000K	<b>W</b> white		<b>C</b> clear lens
			<b>D2</b> triac	<b>38</b> 38°	<b>40</b> 4000K			<b>F</b> frosted lens
			<b>DD</b> DALI		<b>50</b> 5000K			
			<b>CS</b> Casambi					



+61 (03) 9790 8999  
lighting@verbatim.com.au  
www.verbatimlighting.com.au



information is subject to change without prior notice. images are for illustrative purposes only

# smooth M




## vue series

a dark-light effect can create a soft and warm environment, and a curved edge transitions from light to dark gently. the overall effect being to draw the eye to the lit area or object.

the smooth range of architectural luminaires aims to provide the designer with the tools to create the perfect environment to connect with the end user. smooth is complimented with medium to large wattages and adjustable options.

### specifications

system wattage:	16W
luminaire output:	1573lm to 1663lm
CCT:	2700K, 3000K, 3500K, 4000K
optics:	15°, 25°, 40°, 60°
CRI:	90
control:	non-dim, 1-10V, triac, DALI, Casambi
operating voltage:	240Vac
finish:	white & black
housing:	die-cast aluminium & specular aluminium reflector
diffuser:	glass lens
enclosure protection:	IP20/IP44
operating temp:	25°C
lifetime:	50,000hrs
warranty:	5 years
accessories:	honeycomb filter, clear lens, frosted diffuser



### product code

product group	group designation	dimmable	optics	cct	fixture colour	mounting	tilt	accessories
<b>FV</b> vue	<b>SMM-16</b> smooth M-16	<b>X</b>	<b>X</b>	<b>X</b>	<b>X</b>	<b>R</b>	<b>X</b>	<b>X</b>
<b>FV</b>	<b>SMM-16</b>	<b>D0</b> non-dim	<b>15</b> 15°	<b>27</b> 2700K	<b>B</b> black	<b>R</b> recessed	<b>F</b> fixed	<b>H</b> honeycomb filter
		<b>D1</b> 1-10V	<b>25</b> 25°	<b>30</b> 3000K	<b>W</b> white		<b>A</b> adjustable	<b>C</b> clear lens
		<b>D2</b> triac	<b>40</b> 40°	<b>35</b> 3500K				<b>F</b> frosted lens
		<b>DD</b> DALI	<b>60</b> 60°	<b>40</b> 4000K				
		<b>CS</b> Casambi						

# smooth L


vue series



a dark-light effect can create a soft and warm environment, and a curved edge transitions from light to dark gently. the overall effect being to draw the eye to the lit area or object. the smooth range of architectural luminaires aims to provide the designer with the tools to create the perfect environment to connect with the end user. smooth is complimented with medium to large wattages and adjustable options.

## specifications

system wattage:	33W
luminaire output:	3148lm to 3322lm
CCT:	2700K, 3000K, 3500K, 4000K
optics:	15°, 30°, 60°
CRI:	90
control:	non-dim, 1-10V, triac, DALI, Casambi
operating voltage:	240Vac
finish:	white & black
housing:	die-cast aluminium & specular aluminium reflector
diffuser:	glass lens
enclosure protection:	IP20/IP44
operating temp:	25°C
lifetime:	50,000hrs
warranty:	5 years
accessories:	honeycomb filter, clear lens, frosted diffuser



## product code

product group	group designation	wattage	dimming	optics	cct	fixture colour	mounting	accessories
<b>FV</b> vue	<b>SML</b> smooth L	<b>33</b> 33W	<b>X</b>	<b>X</b>	<b>X</b>	<b>X</b>	<b>R</b>	<b>X</b>
<b>FV</b>			<b>D0</b> non-dim	<b>15</b> 15°	<b>27</b> 2700K	<b>B</b> black	<b>R</b> recessed	<b>H</b> honeycomb filter
			<b>D1</b> 1-10V	<b>25</b> 25°	<b>30</b> 3000K	<b>W</b> white		<b>C</b> clear lens
			<b>D2</b> triac	<b>40</b> 40°	<b>35</b> 3500K			<b>F</b> frosted lens
			<b>DD</b> DALI	<b>60</b> 60°	<b>40</b> 4000K			
			<b>CS</b> Casambi					



+61 (03) 9790 8999  
lighting@verbatim.com.au  
www.verbatimlighting.com.au



information is subject to change without prior notice. images are for illustrative purposes only

# vue micro


## vue series

the vue micro range is suitable for residential, retail or commercial projects. Tiny 33mm pin points of light that are discrete yet effective, with options from 15° up to 40°, and a wall-washer reflector. the vue micro ELG adjustable 6W has a deepset light source with a black reflector to eliminate glare and provides a tilt of up to 25°.

### specifications

system wattage:	2W, 6W, 8W
luminaire output:	213lm to 615lm
CCT:	2700K, 3000K, 4000K
optics:	15°, 30°, 40°, wall-wash (adjustable 15°, 25°, 40°)
CRI:	>90
control:	non-dim, 1-10V, triac, DALI, Casambi
operating voltage:	240Vac
finish:	white & black
housing:	die-cast aluminium, reflector or lens
diffuser:	glass lens
enclosure protection:	IP20
operating temp:	25°C
lifetime:	50,000hrs
warranty:	5 years
accessories:	honeycomb filter, clear lens, frosted lens, extra low-glare adjustable

**for**lite



### product code

product group	group designation	wattage	dimmmable	optics	cct	fixture colour	mounting	accessories
<b>FV</b> vue	<b>M</b> micro	<b>2</b> 2W <b>6</b> 6W <b>8</b> 8W	<b>D0</b> non-dim <b>D1</b> 1-10V <b>D2</b> triac <b>DD</b> DALI <b>CS</b> Casambi	<b>15</b> 15° <b>30</b> 30° <b>40</b> 40° <b>WW</b> wallwash	<b>27</b> 2700K <b>30</b> 3000K <b>40</b> 4000K	<b>B</b> black <b>W</b> white	<b>R</b> recessed	<b>H</b> honeycomb filter <b>C</b> clear lens <b>F</b> frosted lens
<b>FV</b> vue	<b>MV</b> micro adjustable	<b>6</b> 6W	<b>D0</b> non-dim <b>D1</b> 1-10V <b>D2</b> triac <b>DD</b> DALI <b>CS</b> Casambi	<b>15</b> 15° <b>25</b> 25° <b>38</b> 38°	<b>27</b> 2700K <b>30</b> 3000K <b>40</b> 4000K	<b>B</b> black <b>W</b> white	<b>R</b> recessed	<b>H</b> honeycomb filter <b>C</b> clear lens <b>F</b> frosted lens

**for**lite

+61 (03) 9790 8999  
lighting@verbatim.com.au  
www.verbatimlighting.com.au

**Verbatim**

# silver XS


vue series



architectural lighting requires the right luminaire. highlighting and accenting with multiple sources rather than just flooding an area with light. the silver XS has a subtle aperture to minimise visual impact, and with an adjustable specular aluminium reflector and a range of beam angles to create the perfect effect.

## specifications

system wattage:	7W
luminaire output:	505lm to 562lm
CCT:	2700K, 3000K, 3500K, 4000K
optics:	20°, 35°, 55°
CRI:	90
control:	non-dim, 1-10V, triac, DALI, Casambi
operating voltage:	240Vac
finish:	white & black
housing:	die-cast aluminium & specular aluminium reflector
diffuser:	glass lens
enclosure protection:	IP20
operating temp:	25°C
lifetime:	50,000hrs
warranty:	5 years
accessories:	honeycomb filter, frosted diffuser



## product code

product group	group designation	wattage	dimmable	optics	cct	fixture colour	mounting	accessories
<b>FV</b> vue	<b>SXS</b> silver XS	<b>7</b> 7W	<b>X</b>	<b>X</b>	<b>X</b>	<b>X</b>	<b>R</b>	<b>X</b>
<b>FV</b>			<b>D0</b> non-dim	<b>20</b> 20°	<b>27</b> 2700K	<b>B</b> black	<b>R</b> recessed	<b>H</b> honeycomb filter
			<b>D1</b> 1-10V	<b>35</b> 35°	<b>30</b> 3000K	<b>W</b> white		<b>F</b> frosted lens
			<b>D2</b> triac	<b>55</b> 55°	<b>35</b> 3500K			
			<b>DD</b> DALI		<b>40</b> 4000K			
			<b>CS</b> Casambi					



+61 (03) 9790 8999  
lighting@verbatim.com.au  
www.verbatimlighting.com.au



information is subject to change without prior notice. images are for illustrative purposes only

# silver S


vue series



architectural lighting requires the right luminaire. highlighting and accenting with multiple sources rather than just flooding an area with light. the silver S has an adjustable specular aluminium reflector and a range of beam angles and washers to create the perfect effect. the range also includes a square trim and trimless options in both square and round trim.

## specifications

system wattage:	15.5W
luminaire output:	1103lm to 1229lm
CCT:	2700K, 3000K, 3500K, 4000K
optics:	25°, 38°, 55°, wallwash
CRI:	90
control:	non-dim, 1-10V, triac, DALI, Casambi
operating voltage:	240Vac
finish:	white & black
housing:	die-cast aluminium & specular aluminium reflector
diffuser:	glass lens
enclosure protection:	IP20
operating temp:	25°C
lifetime:	50,000hrs
warranty:	5 years
accessories:	honeycomb filter, clear lens, frosted diffuser
available on request:	specular, frosted or gold reflector; square, trimless



## product code

product group	group designation	wattage	dimming	optics	cct	fixture colour	mounting	accessories
<b>FV</b> vue	<b>SS</b> silver S	<b>15</b> 15.5W	<b>X</b>	<b>X</b>	<b>X</b>	<b>X</b>	<b>R</b>	<b>X</b>
<b>FV</b>	<b>SS</b>	<b>15</b>	<b>D0</b> non-dim <b>D1</b> 1-10V <b>D2</b> triac <b>DD</b> DALI <b>CS</b> Casambi	<b>25</b> 25° <b>38</b> 38° <b>55</b> 55° <b>WW</b> wallwash	<b>27</b> 2700K <b>30</b> 3000K <b>35</b> 3500K <b>40</b> 4000K	<b>B</b> black <b>W</b> white	<b>R</b> recessed	<b>H</b> honeycomb filter <b>C</b> clear lens <b>F</b> frosted lens



+61 (03) 9790 8999  
lighting@verbatim.com.au  
www.verbatimlighting.com.au



information is subject to change without prior notice. images are for illustrative purposes only

# silver S TW


vue series



architectural lighting requires the right luminaire. highlighting and accenting with multiple sources rather than just flooding an area with light. the silver S TW has an adjustable specular aluminium reflector and a range of beam angles and washers to create the perfect effect. the range also includes a square trim and trimless options in both square and round trim, and all with the flexibility to adjust the colour temperature between 2700K and 6500K.

## specifications

system wattage:	8.7W
luminaire output:	572lm to 679lm
CCT:	tunable white: 2700K - 6500K
optics:	16°, 25°, 38°, 55°, wallwash
CRI:	90
control:	non-dim, 1-10V, triac, DALI, Casambi
operating voltage:	240Vac
finish:	white & black
housing:	die-cast aluminium & specular aluminium reflector
diffuser:	glass lens
enclosure protection:	IP20
operating temp:	25°C
lifetime:	50,000hrs
warranty:	5 years
accessories:	honeycomb filter, clear lens, frosted diffuser
available on request:	specular, frosted or gold reflector; square, trimless



## product code

product group	group designation	wattage	dimming	optics	cct	fixture colour	mounting	accessories
<b>FV</b> vue	<b>SS</b> silver S	<b>8</b> 8.7W	<b>X</b>	<b>X</b>	<b>TW</b> tunable white	<b>X</b>	<b>R</b> recessed	<b>X</b>
			<b>Do</b> non-dim	<b>16</b> 16°		<b>B</b> black		<b>H</b> honeycomb filter
			<b>D1</b> 1-10V	<b>25</b> 25°		<b>W</b> white		<b>C</b> clear lens
			<b>D2</b> triac	<b>38</b> 38°				<b>F</b> frosted lens
			<b>DD</b> DALI	<b>55</b> 55°				
			<b>CS</b> Casambi	<b>WW</b> wallwash				



+61 (03) 9790 8999  
lighting@verbatim.com.au  
www.verbatimlighting.com.au



information is subject to change without prior notice. images are for illustrative purposes only

# silver M


vue series



architectural lighting requires the right luminaire. highlighting and accenting with multiple sources rather than just flooding an area with light. the silver M has an adjustable specular aluminium reflector and a range of beam angles and washers to create the perfect effect. the range also includes a square trim and trimless options in both square and round trim.

## specifications

system wattage:	31W
luminaire output:	2375lm to 2646lm
CCT:	2700K, 3000K, 3500K, 4000K
optics:	16°, 25°, 38°, 55°, wallwash
CRI:	90
control:	non-dim, 1-10V, triac, DALI, Casambi
operating voltage:	240Vac
finish:	white & black
housing:	die-cast aluminium & specular aluminium reflector
diffuser:	glass lens
enclosure protection:	IP20
operating temp:	25°C
lifetime:	50,000hrs
warranty:	5 years
accessories:	honeycomb filter, clear lens, frosted diffuser
available on request:	specular, frosted or gold reflector; square, trimless



## product code

product group	group designation	wattage	dimming	optics	cct	fixture colour	mounting	accessories
<b>FV</b> vue	<b>SM</b> silver M	<b>31</b> 31W	<b>X</b>	<b>X</b>	<b>X</b>	<b>X</b>	<b>R</b>	<b>X</b>
<b>FV</b>	<b>SM</b>	<b>31</b>	<b>D0</b> non-dim	<b>16</b> 16°	<b>27</b> 2700K	<b>B</b> black	<b>R</b> recessed	<b>H</b> honeycomb filter
			<b>D1</b> 1-10V	<b>25</b> 25°	<b>30</b> 3000K	<b>W</b> white		<b>C</b> clear lens
			<b>D2</b> triac	<b>38</b> 38°	<b>35</b> 3500K			<b>F</b> frosted lens
			<b>DD</b> DALI	<b>55</b> 55°	<b>40</b> 4000K			
			<b>CS</b> Casambi	<b>WW</b> wallwash				



+61 (03) 9790 8999  
lighting@verbatim.com.au  
www.verbatimlighting.com.au



information is subject to change without prior notice. images are for illustrative purposes only

# silver M TW


vue series



architectural lighting requires the right luminaire. highlighting and accenting with multiple sources rather than just flooding an area with light. the silver M TW has an adjustable specular aluminium reflector and a range of beam angles and washers to create the perfect effect. the range also includes a square trim and trimless options in both square and round trim, and all with the flexibility to adjust the colour temperature between 2700K and 6500K.

## specifications

system wattage:	19.5W
luminaire output:	1543lm to 1845lm
CCT:	tunable white: 2700K - 6500K
optics:	16°, 25°, 38°, 55°, wallwash
CRI:	90
control:	non-dim, 1-10V, triac, DALI, Casambi
operating voltage:	240Vac
finish:	white & black
housing:	die-cast aluminium & specular aluminium reflector
diffuser:	glass lens
enclosure protection:	IP20
operating temp:	25°C
lifetime:	50,000hrs
warranty:	5 years
accessories:	honeycomb filter, clear lens, frosted diffuser
available on request:	specular, frosted or gold reflector; square, trimless



## product code

product group	group designation	wattage	dimming	optics	cct	fixture colour	mounting	accessories
<b>FV</b> vue	<b>SM</b> silver M	<b>19</b> 19.5W	<b>X</b>	<b>X</b>	<b>TW</b> tunable white	<b>X</b>	<b>R</b> recessed	<b>X</b>
<b>FV</b>	<b>SM</b>	<b>8</b>	<b>D0</b> non-dim <b>D1</b> 1-10V <b>D2</b> triac <b>DD</b> DALI <b>CS</b> Casambi	<b>16</b> 16° <b>25</b> 25° <b>38</b> 38° <b>55</b> 55° <b>WW</b> wallwash	<b>TW</b>	<b>B</b> black <b>W</b> white	<b>R</b>	<b>H</b> honeycomb filter <b>C</b> clear lens <b>F</b> frosted lens



+61 (03) 9790 8999  
lighting@verbatim.com.au  
www.verbatimlighting.com.au



information is subject to change without prior notice. images are for illustrative purposes only

# silver L


vue series



a high wattage solution suitable for high ceilings in open areas.  
a specular aluminium reflector minimises glare and the high CRI and tight colour consistency provides a maintained high quality light throughout the lifetime of the project.

## specifications

system wattage:	34W, 51W, 85W
luminaire output:	3148lm, 7938lm
CCT:	2700K, 3000K, 3500K, 4000K
optics:	40°, 60°
CRI:	90
control:	non-dim, 1-10V, Triac, DALI, Casambi
operating voltage:	240Vac
finish:	white, black
housing:	die-cast aluminium, AL reflector
diffuser:	high transparency optical lens
enclosure protection:	IP20/IP44
operating temp:	25°C
lifetime:	50,000hrs
warranty:	5 years
accessories:	honeycomb filter, clear lens, frosted lens



## product code

product group	group designation	wattage	dimming	beam angle	cct	fixture colour	mounting
<b>FV</b> vue	<b>SL</b> silver L	<b>34</b> 34W <b>51</b> 51W <b>85</b> 85W	<b>Do</b> non-dim <b>D1</b> 1-10V <b>D2</b> TRIAC <b>DD</b> DALI <b>CS</b> Casambi	<b>40</b> 40° <b>60</b> 60°	<b>27</b> 2700K <b>30</b> 3000K <b>35</b> 3500K <b>40</b> 4000K	<b>W</b> white <b>B</b> black	<b>R</b> recessed



+61 (03) 9790 8999  
lighting@verbatim.com.au  
www.verbatimlighting.com.au



information is subject to change without prior notice. images are for illustrative purposes only

# quantum

## vue series


the quantum uses a narrow aperture body to project light across a wide area while limiting glare. trim options of black or white and a reflector in black provide a smooth transition from ceiling to light source.

the quantum has a simple yet elegant design and the blend of quality components and high-CRI light sources elevates the quantum above the pack.



### specifications

system wattage:	3W, 6W, 10W, 20W, 30W
luminaire output:	160lm - 2100lm
CCT:	2700K, 3000K, 3500K, 4000K
optics:	15°, 30°, 45°, wall-wash in 10W upwards
CRI:	>90
control:	non-dim, 1-10V, Triac, DALI, Casambi
operating voltage:	240Vac
finish:	white, black
housing:	aluminium and PC
diffuser:	high transparency optical lens
enclosure protection:	IP20
operating temp:	25°C
lifetime:	40,000hrs
warranty:	5 years
accessories:	N/A



### product code

product group	group designation	wattage	dimming	beam angle	cct	fixture colour	mounting
<b>FV</b> vue	<b>Q</b> quantum	<b>3</b> 3W	<b>Do</b> non-dim	<b>15</b> 15°	<b>27</b> 2700K	<b>W</b> white	<b>R</b> recessed
		<b>6</b> 6W	<b>D1</b> 1-10V	<b>30</b> 30°	<b>30</b> 3000K	<b>B</b> black	
		<b>10</b> 10W	<b>D2</b> TRIAC	<b>45</b> 45°	<b>35</b> 3500K		
		<b>20</b> 20W	<b>DD</b> DALI	<b>WW</b> wallwash	<b>40</b> 4000K		
		<b>30</b> 30W	<b>CS</b> Casambi				



+61 (03) 9790 8999  
lighting@verbatim.com.au  
www.verbatimlighting.com.au



information is subject to change without prior notice. images are for illustrative purposes only

# quantum IP65

vue series




the quantum uses a narrow aperture body to project light across a wide area while limiting glare. trim options of black or white and a reflector in black provide a smooth transition from ceiling to light source. IP65 rated version make it suitable to use in wet areas.

the quantum has a simple yet elegant design and the blend of quality components and high-CRI light sources elevates the quantum above the pack. the quantum IP65 is supplied with a remote driver (IP20 unless requested otherwise requested).



## specifications

system wattage:	10W, 20W, 30W
luminaire output:	800lm (10W), 1300lm (20W), 2150lm (30W)
CCT:	2700K, 3000K, 4000K, 5000K
optics:	15°, 30°, 45°
CRI:	>90
control:	non-dim, 1-10V, Triac, DALI, Casambi
operating voltage:	240Vac
finish:	white, black
housing:	aluminium and PC
diffuser:	high transparency optical lens
enclosure protection:	IP20
operating temp:	25°C
lifetime:	40,000hrs
warranty:	5 years
accessories:	N/A



## product code

product group	group designation	wattage	dimnable	beam angle	cct	fixture colour	mounting
<b>FV</b> vue	<b>QW</b> quantum IP65	<b>10</b> 10W <b>20</b> 20W <b>30</b> 30W	<b>Do</b> non-dim <b>D1</b> 1-10V <b>D2</b> TRIAC <b>DD</b> DALI <b>CS</b> Casambi	<b>15</b> 15° <b>30</b> 30° <b>45</b> 45°	<b>27</b> 2700K <b>30</b> 3000K <b>35</b> 3500K <b>40</b> 4000K	<b>W</b> white <b>B</b> black	<b>R</b> recessed



+61 (03) 9790 8999  
lighting@verbatim.com.au  
www.verbatimlighting.com.au



information is subject to change without prior notice. images are for illustrative purposes only

# kub S

vue series








kub small is a square recessed downlight, compact and elegant design, easy for installation. using the latest high quality LED technology.

it's suitable for office buildings, shopping malls, hotels, exhibition centres or retail applications.

## specifications

system wattage:	10W in single, double or triple
luminaire output:	80lm/W
CCT:	2700K, 3000K, 4000K
optics:	15°, 24°, 40°
CRI:	>90
control:	non-dim, DALI, 1-10V, Casambi
operating voltage:	240Vac
finish:	white, black
housing:	aluminium and steel
diffuser:	high transparency optical lens
enclosure protection:	IP20
operating temp:	25°C
lifetime:	40,000hrs
warranty:	5 years
accessories:	N/A



## product code

product group	group designation	wattage	dimmable	beam angle	cct	fixture colour	mounting
<b>FV</b> vue	<b>KS</b> kub small	<b>10</b> 10W	<b>D0</b> non-dim	<b>15</b> 15°	<b>27</b> 2700K	<b>W</b> white	<b>R</b> recessed
		<b>210</b> 2 x 10W	<b>D1</b> 1-10V	<b>24</b> 24°	<b>30</b> 3000K	<b>B</b> black	
		<b>310</b> 3 x 10W	<b>D2</b> TRIAC	<b>40</b> 40°	<b>40</b> 4000K		
			<b>DD</b> DALI				
			<b>CS</b> Casambi				



+61 (03) 9790 8999  
lighting@verbatim.com.au  
www.verbatimlighting.com.au




information is subject to change without prior notice. images are for illustrative purposes only

# kub L

## vue series




kub large is a square recessed downlight, compact and elegant design, easy for installation. using the latest high quality LED technology.

it's suitable for office buildings, shopping malls, hotels, exhibition centres or retail applications.



### specifications

system wattage:	20W or 30W in single, double or triple
luminaire output:	70lm/W
CCT:	2700K, 3000K, 4000K
optics:	15°, 24°, 40°
CRI:	>90
control:	non-dim, DALI, 1-10V, Casambi
operating voltage:	240Vac
finish:	white, black
housing:	aluminium and steel
diffuser:	high transparency optical lens
enclosure protection:	IP20
operating temp:	25°C
lifetime:	40,000hrs
warranty:	5 years
accessories:	N/A



### product code

product group	group designation	wattage	dimming	beam angle	cct	fixture colour	mounting
<b>FV</b> vue	<b>KL</b> kub large	<b>20</b> 20W	<b>D0</b> non-dim	<b>15</b> 15°	<b>27</b> 2700K	<b>W</b> white	<b>R</b> recessed
		<b>30</b> 30W	<b>D1</b> 1-10V	<b>24</b> 24°	<b>30</b> 3000K	<b>B</b> black	
		<b>220</b> 2 x 20W	<b>D2</b> TRIAC	<b>40</b> 40°	<b>40</b> 4000K		
		<b>230</b> 2 x 30W	<b>DD</b> DALI				
		<b>320</b> 3 x 20W	<b>CS</b> Casambi				
		<b>330</b> 3 x 30W					



+61 (03) 9790 8999  
lighting@verbatim.com.au  
www.verbatimlighting.com.au



# elpin

## vue series

the elpin range provides a low glare architectural solution for a variety of internal and external spaces.

the surface mounted aluminium housing is powder coated in a matte finish complete with a matching satin low glare reflector and TIR lens.


the elpin family offers a variety of sizes, colour temperatures and lumen packages, all with concealed fixings and integral drivers for non-Dali fittings.

### specifications

system wattage:	see table below
luminaire output:	see table below
CCT:	2700K, 3000K, 4000K, 5000K
optics:	20°, 40°
CRI:	IP20: 90CRI; IP65: 80CRI
control:	non-dim, Triac, DALI or 1-10V
operating voltage:	240Vac
finish:	black, white
housing:	die-cast aluminium
diffuser:	polycarbonate
enclosure protection:	IP20 or IP65
operating temp:	25°C
lifetime:	50,000hrs
warranty:	5 years
accessories:	N/A

Watts (W)	Dimensions (mm)		Lumens (lm)
	diameter (A)	height (B)	
10	75	100	666
20	115	152	1329
30	140	162	2025
50	205	212	3550
70	205	212	4970

**for**lite



available in 5 sizes- refer to table  
for product dimensions

### product code

product group	group designation	wattage	dimming	beam angle	cct	fixture colour	mounting
<b>FV</b> vue	<b>E20</b> elpin IP20 <b>E65</b> elpin IP65	<b>10</b> 10W <b>20</b> 20W <b>30</b> 30W <b>50</b> 50W <b>70</b> 70W	<b>D0</b> non-dim <b>D1</b> 1-10V <b>D2</b> TRIAC <b>DD</b> DALI	<b>20</b> 20° <b>40</b> 40°	<b>27</b> 2700K <b>30</b> 3000K <b>40</b> 4000K <b>50</b> 5000K	<b>W</b> white <b>B</b> black	<b>S</b> surface

**for**lite

+61 (03) 9790 8999  
lighting@verbatim.com.au  
www.verbatimlighting.com.au


**Verbatim**

information is subject to change without prior notice. images are for illustrative purposes only

the vue polo range is suitable for residential, retail or commercial projects. surface mount downlight comes with specular finish gloss reflector in aluminum vacuum coated and die cast aluminum housing. Citizen LED COB with 40° and 60° beam angle options.

### specifications

system wattage:	10W, 20W
luminaire output:	1020lm, 2031lm
CCT:	2700K, 3000K, 3500K, 4000K
optics:	40°, 50°
CRI:	>90
control:	non-dim, 1-10V, Triac, DALI
operating voltage:	240Vac
finish:	white, black
housing:	die-cast aluminium, AL reflector
diffuser:	high transparency optical lens
enclosure protection:	IP20
operating temp:	25°C
lifetime:	50,000hrs
warranty:	5 years
accessories:	ceiling bracket, clear lens, frosted lens



### product code

product group	group designation	wattage	dimming	beam angle	cct	fixture colour	mounting
<b>FV</b> vue	<b>P</b> polo	<b>10</b> 10W <b>20</b> 20W	<b>Do</b> non-dim <b>D1</b> 1-10V <b>D2</b> TRIAC <b>DD</b> DALI	<b>40</b> 40° <b>60</b> 60°	<b>27</b> 2700K <b>30</b> 3000K <b>35</b> 3500K <b>40</b> 4000K	<b>W</b> white <b>B</b> black	<b>S</b> surface mounted

# polo adjustable

vue series




the polo is a compact surface-mounted downlight with an adjustable extra-low glare optical chamber.

perfect for residential or commercial applications such as lobbys, foyers, or break-out spaces.

## specifications

system wattage:	10W, 15W
luminaire output:	600lm, 900lm
CCT:	2700K, 3000K, 4000K
optics:	25°, 40°, 50°
CRI:	>90
control:	non-dim, DALI, 1-10V, Casambi
operating voltage:	240Vac
finish:	white, black
housing:	aluminium
diffuser:	high transparency optical lens
enclosure protection:	IP20
operating temp:	25°C
lifetime:	40,000hrs
warranty:	5 years
accessories:	N/A



## product code

product group	group designation	wattage	dimmable	beam angle	cct	fixture colour	mounting
<b>FV</b> vue	<b>PA</b> polo adjustable <b>PS</b> polo square	<b>10</b> 10W <b>15</b> 15W	<b>Do</b> non-dim <b>D1</b> 1-10V <b>D2</b> TRIAC <b>DD</b> DALI <b>CS</b> Casambi	<b>25</b> 25° <b>40</b> 40° <b>50</b> 50°	<b>27</b> 2700K <b>30</b> 3000K <b>40</b> 4000K	<b>W</b> white <b>B</b> black	<b>S</b> surface mounted



+61 (03) 9790 8999  
lighting@verbatim.com.au  
www.verbatimlighting.com.au



information is subject to change without prior notice. images are for illustrative purposes only

# slim pendant


teso series



the teso slim pendant light is a unique and modern addition for home, hospitality, or retail. the sleek design gives the teso slim has a clean contemporary feel that will add sophistication to any room. it's perfect for hanging over counters, tables, desks, and other areas where you want to make a statement. the adjustable height makes it easy to customise the look of your space while providing ample illumination. whether you're looking for something stylish or functional, the teso slim pendant light is sure to be the perfect fit.

## specifications

system wattage:	15W or 21W
luminaire output:	1514lm (15W); 2031lm (21W)
CCT:	3000K, 3500K, 4000K
optics:	15°, 25°, 40°, 60°
CRI:	>90
control:	non-dim, 1-10V, TRIAC, DALI
operating voltage:	240Vac
finish:	white, black
housing:	aluminium
diffuser:	glass lens
enclosure protection:	IP20
operating temp:	-20°C to +40°C
lifetime:	50,000hrs
warranty:	5 years
accessories:	honeycomb filter, clear lens, frosted lens



## product code

product group	group designation	wattage	dimmmable	beam angle	cct	fixture colour	mounting	accessories
<b>FT</b> teso	<b>S</b> slim	<b>15</b> 15W <b>21</b> 21W	<b>D0</b> non-dim <b>D1</b> 1-10V <b>D2</b> TRIAC <b>DD</b> DALI	<b>15</b> 15° <b>25</b> 25° <b>40</b> 40° <b>60</b> 60°	<b>30</b> 3000K <b>35</b> 3500K <b>40</b> 4000K	<b>B</b> black <b>W</b> white	<b>PF</b> pendant flex <b>PW</b> pendant wire	<b>H</b> honeycomb filter <b>C</b> clear lens <b>F</b> frosted lens



+61 (03) 9790 8999  
lighting@verbatim.com.au  
www.verbatimlighting.com.au



information is subject to change without prior notice. images are for illustrative purposes only

# float round

## vue series



the float round series offers a minimalistic, low profile circular design suitable for large indoor spaces.

designed with a micro prismatic diffuser for low glare illumination available in a variety of sizes and lumen packages.

float round can be ceiling, wall mounted or suspended with the option of direct only or direct/indirect illumination.

### specifications


system wattage:	see table below
luminaire output:	see table below
CCT:	3000K, 4000K
optics:	120° for direct
CRI:	>90
control:	fixed, triac, DALI or Casambi
operating voltage:	240Vac
finish:	white or black
housing:	aluminium
diffuser:	microprismatic
enclosure protection:	IP66, IK10
operating temp:	-20°C to +40°C
lifetime:	50,000hrs
warranty:	5 years
accessories:	N/A



wire suspended



surface-mount



available in 4 sizes- refer to table for product dimensions

Watts (W)	Dimensions (mm)		Lumens (lm)
	A	B	
40	400	219	4300
60	600	383	6500
80	800	383	8600
100	1000	383	10800

### product code

product group	group destination	distribution	size	dimming	cct	fixture colour	mounting
<b>FV</b> vue	<b>FR</b> float round	<b>X</b>	<b>X</b>	<b>X</b>	<b>X</b>	<b>X</b>	<b>X</b>
<b>FV</b>	<b>FR</b>	<b>D</b> direct <b>DI</b> direct/indirect	<b>1000</b> 1000mm <b>800</b> 800mm <b>600</b> 600mm <b>400</b> 400mm	<b>Do</b> non-dim <b>D2</b> TRIAC <b>DD</b> DALI <b>CS</b> Casambi	<b>30</b> 3000K <b>40</b> 4000K	<b>W</b> white <b>B</b> black	<b>S</b> surface <b>PW</b> pendant wire <b>PR</b> pendant rod



+61 (03) 9790 8999  
lighting@verbatim.com.au  
www.verbatimlighting.com.au



# float square

vue series




the float square has a large profile with a simple yet elegant design. the specialist optic includes a secondary light distribution with a 120° wide beam angle. at just 70mm in depth the overall effect is of a floating light source.


float square is available as a pendant with rod or wire, but can also be supplied as a wall or ceiling mount. direct or direct/in-direct lighting effects are available, to allow for a soft ambient atmosphere.

## specifications

system wattage:	see table below
luminaire output:	see table below
CCT:	3000K, 4000K
beam angle:	120°
CRI:	90
control:	non-dim, DALI
operating voltage:	240Vac
finish:	white or black
housing:	aluminium and PC
diffuser:	PVC soft film
enclosure protection:	IP20
operating temp:	-20°C to +40°C
lifetime:	50,000hrs
warranty:	5 years
accessories:	N/A



available in 3 sizes- refer to table for product dimensions



pendant wire

watts (W)	dimensions (mm)		lumens (lm)
	A	B	
60	900	900	4450
60	1200	1200	4050-4450
80	1500	1500	5700-6400

## product code

product group	group destination	size	dimmmable	cct	fixture colour	mounting
<b>FV</b> vue	<b>F</b> float square	<b>X</b>	<b>X</b>	<b>X</b>	<b>X</b>	<b>X</b>
<b>FV</b>	<b>FS</b>	<b>90</b> 900mm	<b>Do</b> non-dim	<b>30</b> 3000K	<b>W</b> white	<b>S</b> surface
		<b>120</b> 1200mm	<b>DD</b> DALI	<b>40</b> 4000K	<b>B</b> black	<b>PW</b> pendant wire
		<b>150</b> 1500mm				



+61 (03) 9790 8999  
lighting@verbatim.com.au  
www.verbatimlighting.com.au



information is subject to change without prior notice. images are for illustrative purposes only

# ligne circular

vue series




the ligne circular pendant range offers a decorative architectural solution for larger indoor spaces.

the range of sizes and lumen packages can be combined to create a stunning effect from the ceiling while delivering even ambient illumination.

## specifications

system wattage:	see table below
luminaire output:	see table below
CCT:	3000K, 4000K
optics:	105°
CRI:	>80
control:	non-dim, DALI or casambi (remote driver)
operating voltage:	240Vac
finish:	black
housing:	aluminium & polycarbonate
diffuser:	opal polycarbonate diffuser
enclosure protection:	IP20
operating temp:	-20°C to +40°C
lifetime:	50,000hrs
warranty:	5 years
accessories:	N/A



watts (W)	diameter (mm)	lumens (lm)
35	400	3100-3400
54	600	4900-5300
70	800	6300-6700
84	1000	7600-8000

## product code

product group	group designation	wattage	dimmmable	cct	fixture colour	mounting
<b>FV</b> vue	<b>LC</b> ligne circular	<b>35</b> 35W <b>54</b> 54W <b>70</b> 70W <b>84</b> 84W	<b>Do</b> non-dim <b>DD</b> DALI <b>CS</b> Casambi	<b>30</b> 3000K <b>40</b> 4000K	<b>B</b> black	<b>PW</b> pendant wire



+61 (03) 9790 8999  
lighting@verbatim.com.au  
www.verbatimlighting.com.au



information is subject to change without prior notice. images are for illustrative purposes only

# teso basic 15W

teso series

the teso basic series is suitable for commercial and retail applications.


the clean lines of a track-recessed driver provides a clean minimalist look. being only 52mm in diameter the teso basic has a low aesthetic impact.

high CRI and a tight colour consistency provides a high quality lighting result to compliment any architectural project.

## specifications

system wattage:	15W
luminaire output:	nominal 810lm delivered
CCT:	2700K, 3000K, 3500K, 4000K
optics:	15°, 25°, 40°, 60°
CRI:	90
control:	non-dim, 1-10V, TRIAC, DALI
operating voltage:	240Vac
finish:	white, black
housing:	die-cast aluminium
diffuser:	PC lens
enclosure protection:	IP20
operating temp:	-20°C to +40°C
lifetime:	50,000hrs
warranty:	5 years
accessories:	N/A

 **forlite**



## product code

<b>FT</b>	<b>B</b>	<b>15</b>	<b>X</b>	<b>X</b>	<b>X</b>	<b>X</b>	<b>X</b>
product group	group designation	wattage	dimmable	beam angle	cct	fixture colour	mounting
<b>FT</b> teso	<b>B</b> basic	<b>15</b> 15W	<b>D0</b> non-dim <b>D1</b> 1-10V <b>D2</b> TRIAC <b>DD</b> DALI	<b>15</b> 15° <b>25</b> 25° <b>40</b> 40° <b>60</b> 60°	<b>27</b> 2700K <b>30</b> 3000K <b>35</b> 3500K <b>40</b> 4000K	<b>B</b> black <b>W</b> white	<b>T</b> track

 **forlite**

+61 (03) 9790 8999  
lighting@verbatim.com.au  
www.verbatimlighting.com.au

 **Verbatim**

information is subject to change without prior notice. images are for illustrative purposes only

# teso basic 26W

teso series




the teso basic series is suitable for commercial and retail applications.

the clean lines of a track-recessed driver provides a clean minimalist look. being only 52mm in diameter the teso basic has a low aesthetic impact.

high CRI and a tight colour consistency provides a high quality lighting result to compliment any architectural project.

## specifications

system wattage:	26W
luminaire output:	nominal 1200lm delivered
CCT:	2700K, 3000K, 3500K, 4000K
optics:	15°, 25°, 40°, 60°
CRI:	90
control:	non-dim, 1-10V, TRIAC, DALI
operating voltage:	240Vac
finish:	white, black
housing:	die-cast aluminium
diffuser:	PC lens
enclosure protection:	IP20
operating temp:	-20°C to +40°C
lifetime:	50,000hrs
warranty:	5 years
accessories:	N/A



## product code

product group	group designation	wattage	dimmable	beam angle	cct	fixture colour	mounting
FT	B	26	X	X	X	X	X
FT	B	26	D0	15	27	B	T
teso	basic	26W	non-dim	15°	2700K	black	track
			D1	25	30	W	
			1-10V	25°	3000K	white	
			D2	40	35		
			TRIAC	40°	3500K		
			DD	60	40		
			DALI	60°	4000K		



+61 (03) 9790 8999  
lighting@verbatim.com.au  
www.verbatimlighting.com.au



information is subject to change without prior notice. images are for illustrative purposes only

# teso pro


## teso series

the teso pro range takes commercial and retail applications to the next step. the clean lines of a track-recessed driver provides a clean minimalist look. being only 52mm in diameter the teso pro has a low aesthetic impact.

high CRI and a tight colour consistency provides a high quality lighting result to compliment any architectural project plus the pro has an option for a wireless controlled adjustable beam angles.

### specifications

system wattage:	21W
luminaire output:	nominal 1100lm delivered
CCT:	2700K, 3000K, 3500K, 4000K
optics:	15°, 25°, 40°, 60°
CRI:	90
control:	non-dim, 1-10V, TRIAC, DALI
operating voltage:	240Vac
finish:	white, black
housing:	die-cast aluminium
diffuser:	PC lens
enclosure protection:	IP20
operating temp:	25°C
lifetime:	50,000hrs
warranty:	5 years
accessories:	honeycomb filter, clear lens, frosted lens, snoot



### product code

product group	group designation	wattage	dimmable	beam angle	cct	fixture colour	mounting	accessories
<b>FT</b> teso	<b>P</b> pro	<b>21</b> 21W	<b>X</b>	<b>X</b>	<b>X</b>	<b>X</b>	<b>T</b> track	<b>X</b>
<b>FT</b>			<b>D0</b> non-dim	<b>15</b> 15°	<b>27</b> 2700K	<b>B</b> black		<b>H</b> honeycomb filter
			<b>D1</b> 1-10V	<b>25</b> 25°	<b>30</b> 3000K	<b>W</b> white		<b>C</b> clear lens
			<b>D2</b> TRIAC	<b>40</b> 40°	<b>35</b> 3500K			<b>F</b> frosted lens
			<b>DD</b> DALI	<b>60</b> 60°	<b>40</b> 4000K			<b>S</b> snoot
			<b>CS</b> Casambi					

# ligne-micro


linear micro extrusion



matching miniature extrusion with quality LED boards and strips, the ligne-micro is a quality option for architectural effect lighting. Suited to retail, board-rooms or break-out spaces, the lighting designer can play with light by hiding the light source in architectural elements


## specifications

system wattage:	4W, 8W, 12W, 16W
luminaire output:	600lm to 2500lm
CCT:	2700K, 3000K, 4000K, 6500K
optics:	110°
CRI:	Ra80 or R90
control:	non-dim, 1-10V, DALI, Casambi
operating voltage:	240Vac
finish:	white, silver, black
housing:	
diffuser:	
enclosure protection:	IP20
operating temp:	
lifetime:	50,000hrs
warranty:	5 years
accessories:	




## dimensional drawings


ligne 1616D




ligne 1708D



ligne 1715S



ligne 3535S



## product code

product group	size	wattage	dimming	cct	fixture colour	length (mm)	mounting
<b>FLM</b> ligne-micro	<b>1616</b> 1616D	<b>4</b> 4W	<b>Do</b> non-dim	<b>27</b> 2700K	<b>B</b> black	<b>X</b> length	<b>SM</b> surface-mount
	<b>1708</b> 1708D	<b>8</b> 8W	<b>D1</b> 1-10V	<b>30</b> 3000K	<b>W</b> white		
	<b>1715</b> 1715S	<b>12</b> 12W	<b>DD</b> DALI	<b>40</b> 4000K	<b>S</b> silver		
	<b>3535</b> 3535S	<b>16</b> 16W	<b>CS</b> Casambi	<b>65</b> 6500K			



+61 (03) 9790 8999  
lighting@verbatim.com.au  
www.verbatimlighting.com.au



information is subject to change without prior notice. images are for illustrative purposes only

# artere axis 16


flexible strip light



the axis 16 bends horizontally and vertically, allowing complex irregular shapes – unlike the previous generation which could only bend on one axis. it's IP67 and can be supplied in any length up to 10m, with no pre-defined cutting intervals. it's available in static white colours and tunable white (see axis 23 for RGBW and pixel control options). various mounting options can be selected at time of order, along with a wide variety of dimming and control options.

## specifications

system wattage:	14W/m
luminaire output:	840lm/m @ 14W
CCT:	2700K, 3000K, 3500K, 4000K, 5000K, 6000K, TW
optics:	120°
CRI:	80
control:	non-dim, 1-10V, DALI, Casambi
operating voltage:	24Vdc
finish:	white
housing:	silicon
diffuser:	homogeneous diffuser
enclosure protection:	IP67, IK08
operating temp:	-20°C ~ 45°C
lifetime:	50,000hrs (indoor); 36,000hrs (outdoor)
warranty:	5 years (indoor); 3 years (outdoor)
accessories:	bracket, clip, extrusion, flexible



## product code

product group	group designation	wattage	dimmable	cct	connector	mounting	length
FA artere	A16 axis 16	14 14W/m	Do non-dim D1 1-10V DD DALI CS Casambi	27 2700K 30 3000K 35 3500K 40 4000K 50 5000K 60 6000K TW tunable white	EF end feed RF rear feed SF side feed	B bracket C clip E extrusion F flexible	10 1000mm

note: tunable white requires DALI or Casambi driver



+61 (03) 9790 8999  
lighting@verbatim.com.au  
www.verbatimlighting.com.au



information is subject to change without prior notice. images are for illustrative purposes only




# artere axis 16

flexible strip light






## dimensions / diagram




### end feed



### side feed



### rear feed



+61 (03) 9790 8999  
lighting@verbatim.com.au  
www.verbatimlighting.com.au



information is subject to change without prior notice. images are for illustrative purposes only



# artere axis 16

flexible strip light





## mounting accessories / installation


bracket





clip





aluminium channel



bendable bracket




## bend & twist diagram



Can be top-bend



Can be side-bend



+61 (03) 9790 8999  
lighting@verbatim.com.au  
www.verbatimlighting.com.au



information is subject to change without prior notice. images are for illustrative purposes only

# artere axis 23


flexible strip light



the axis 23 bends horizontally and vertically, allowing complex irregular shapes – unlike the previous generation which could only bend on one axis. it's IP67 and can be supplied in any length up to 10m, with no pre-defined cutting intervals. it's available in static white colours, tunable white, RGBW and pixel RGBW. various mounting options can be selected at time of order, along with a wide variety of dimming and control options.

## specifications

system wattage:	18W/m
luminaire output:	750lm/m @ 18W
CCT:	2700K, 3000K, 3500K, 4000K, 5000K, 6000K, TW, RGBW, RGBW-pixel
optics:	120°
CRI:	80 (CRI 90 available)
control:	non-dim, 1-10V, DALI, DMX, Casambi
operating voltage:	24Vdc
finish:	white
housing:	silicon
diffuser:	homogeneous diffuser
enclosure protection:	IP67, IK08
operating temp:	-20°C ~ 45°C
lifetime:	50,000hrs (indoor); 36,000hrs (outdoor)
warranty:	5 years (indoor); 3 years (outdoor)
accessories:	bracket, clip, extrusion, flexible



## product code

product group	group designation	wattage	dimmable	cct	connector	mounting	length
FA artere	A23 axis 23	18 18W/m*	D0 non-dim D1 1-10V DD DALI DMX DMX CS Casambi	27 2700K 30 3000K 35 3500K 40 4000K 50 5000K 60 6000K TW tunable white RGBW rgbw RGBWP rgbw- pixel	EF end feed RF rear feed SF side feed	B bracket C clip E extrusion F flexible	10 1000mm

note: tunable white requires DALI or Casambi driver  
\* rgbw-pixel option is 14W/m



+61 (03) 9790 8999  
lighting@verbatim.com.au  
www.verbatimlighting.com.au






# artere axis 23

flexible strip light





## dimensions / diagram



### end feed



### side feed



### rear feed



+61 (03) 9790 8999  
lighting@verbatim.com.au  
www.verbatimlighting.com.au



information is subject to change without prior notice. images are for illustrative purposes only



# artere axis 23

flexible strip light




## mounting accessories / installation


bracket





clip




aluminium channel




bendable bracket




## bend & twist diagram



Can be side-bend



Can be top-bend



## accessories

Front Cap (Power cable in rear feed)	Front Cap (Power cable in side feed)	Front Cap (Power cable in bottom feed)	Endcap	Glue



+61 (03) 9790 8999  
lighting@verbatim.com.au  
www.verbatimlighting.com.au



information is subject to change without prior notice. images are for illustrative purposes only

# ario deep




## vue series

the ario deep IP65 is the next generation of fully sealed waterproof downlights from forlite. featuring an internally recessed light source with a high purity anodised aluminium reflector for maximum efficiency and excellent visual comfort. the body is a die-cast aluminium with a powdercoated finish. it is fully sealed front and back - making it bug resistant and supplied with a remote driver (IP20 unless otherwise requested).

### specifications

system wattage:	15W, 26W
luminaire output:	1200lm (15W), 2050lm (25W)
CCT:	2700K, 3000K, 4000K, 5000K
optics:	15°, 24°, 36°, 45°, 60°
CRI:	>90
control:	non-dim, 1-10V, Triac, DALI, Casambi
operating voltage:	240Vac
finish:	white & black, powdercoat finish
housing:	die-cast aluminium, high purity anodised aluminium reflector
diffuser:	clear glass
enclosure protection:	IP65
operating temp:	25°C
lifetime:	50,000hrs
warranty:	5 years
accessories:	N/A

**forlite**



### product code

product group	group designation	wattage	dimming	optics	cct	fixture colour	mounting
<b>FR</b>	<b>AD</b>	<b>X</b>	<b>X</b>	<b>X</b>	<b>X</b>	<b>X</b>	<b>R</b>
<b>FV</b> vue	<b>AD</b> ario deep	<b>15</b> 15W <b>26</b> 26W	<b>D0</b> non-dim <b>D1</b> 1-10V <b>D2</b> Triac <b>DD</b> DALI <b>CS</b> Casambi	<b>15</b> 15° <b>24</b> 24° <b>36</b> 36° <b>45</b> 45° <b>60</b> 60°	<b>27</b> 2700K <b>30</b> 3000K <b>40</b> 4000K <b>50</b> 5000K	<b>B</b> black <b>W</b> white	<b>R</b> recessed

**forlite**

+61 (03) 9790 8999  
lighting@verbatim.com.au  
www.verbatimlighting.com.au

**Verbatim**

# ario gen2



## vue series

the ario gen 2 IP65 is an architectural revelation as an exterior IP-rated downlight. medium sized and IP65 from top and bottom, the ario is bug-resistant and attractive. the use of a multi-faceted reflector reduces glare and night-blindness by hiding the direct view of the light source.

the ario gen 2 is supplied with a remote driver (IP20 unless otherwise requested).

### specifications

system wattage:	26W
luminaire output:	2230lm
CCT:	2700K, 3000K, 4000K, 5000K
optics:	12°, 22°, 36°, 60°
CRI:	80
control:	non-dim, 1-10V, Triac, DALI, Casambi
operating voltage:	240Vac
finish:	white & black, powdercoat finish
housing:	die-cast aluminium, high purity anodised aluminium reflector
diffuser:	clear glass
enclosure protection:	IP65
operating temp:	25°C
lifetime:	50,000hrs
warranty:	5 years
accessories:	N/A



### product code

product group	group designation	wattage	dimmmable	optics	cct	fixture colour	mounting
FR	A	26	X	X	X	X	R
FV	A	26	Do non-dim	12 12°	27 2700K	B black	R recessed
			D1 1-10V	22 22°	30 3000K	W white	
			D2 Triac	36 36°	40 4000K		
			DD DALI	60 60°	50 5000K		
			CS Casambi				

# vue hellion

hellion series




the vue hellion range is suitable for residential, retail or commercial projects.

surface mount downlight comes with specular finish gloss reflector in aluminum vacuum coated and die cast aluminum housing, Citizen LED COB with 40° and 60° beam angle options,



## specifications

system wattage:	20W, 33W, 45W
luminaire output:	2062lm to 4202lm
CCT:	2700K, 3000K, 3500K, 4000K
optics:	40°, 60°
CRI:	>90
control:	non-dim, 1-10V, Triac, DALI
operating voltage:	240Vac
finish:	white & black
housing:	die-cast aluminium, al reflector
diffuser:	
enclosure protection:	IP65
operating temp:	25°C
lifetime:	50,000hrs
warranty:	5 years
accessories:	ceiling bracket



## product code

product group	group designation	wattage	dimmable	optics	cct	fixture colour	mounting
<b>FV</b> vue	<b>H</b> hellion	<b>20</b> 20W <b>33</b> 33W <b>45</b> 45W	<b>D0</b> non-dim <b>D1</b> 1-10V <b>D2</b> triac <b>DD</b> DALI	<b>40</b> 40° <b>60</b> 60°	<b>27</b> 2700K <b>30</b> 3000K <b>35</b> 3500K <b>40</b> 4000K	<b>B</b> black <b>W</b> white	<b>S</b> surface mounted



+61 (03) 9790 8999  
lighting@verbatim.com.au  
www.verbatimlighting.com.au



information is subject to change without prior notice. images are for illustrative purposes only

# hellion small wall


stena series



a large wall light series suitable for decoration lighting, or to enhance the partial effect for building. compact and elegant design, high efficient performance, create a perfect lighting effect. it's widely used for outdoor building decoration and public area lighting.

## specifications

system wattage:	5W, 2x5W
luminaire output:	230lm (5W)
CCT:	2700K, 3000K, 4000K
optics:	15°, 24°, 38°
CRI:	>80
control:	non-dim
operating voltage:	240Vac
finish:	white & black
housing:	aluminium
diffuser:	safety tempered glass
enclosure protection:	IP65
operating temp:	25°C
lifetime:	50,000hrs
warranty:	5 years
accessories:	N/A



## product code

product group	group designation	wattage	dimming	optics	cct	fixture colour	mounting
FS	HS		Do	X	X	X	W
FS	stena	5	Do	15	27	B	W
	hellion small	25	non-dim	24	30	W	wall mounted
				38	40		



+61 (03) 9790 8999  
lighting@verbatim.com.au  
www.verbatimlighting.com.au



information is subject to change without prior notice. images are for illustrative purposes only

# hellion medium wall

stena series




introducing the hellion wall IP65 wall mounted range. featuring a contemporary design, this luminaire is perfect for a variety of outdoor applications such as illuminating walkways, building exteriors, and parking areas. with its various optics and wattages it is possible to easily customise the lighting to fit specific needs.

with its high-quality die-cast aluminium construction and integral driver, the hellion wall is the perfect choice to enhance outdoor areas.

## specifications

system wattage:	20W, 30W, 2x15W
luminaire output:	1600lm (20W) 2400lm (30W) 2x1200lm (2x15W)
CCT:	2700K, 3000K, 4000K
optics:	15°, 25°, 38°, 45°, 60°
CRI:	>80
control:	non-dim
operating voltage:	240Vac
finish:	white & black
housing:	aluminium
diffuser:	safety tempered glass
enclosure protection:	IP65
operating temp:	25°C
lifetime:	50,000hrs
warranty:	5 years
accessories:	N/A



## product code

product group	group designation	wattage	dimmable	optics	cct	fixture colour	mounting
<b>FS</b> stena	<b>HL</b> hellion medium	<b>20</b> 20W <b>30</b> 30W <b>215</b> 2x15W	<b>Do</b> non-dim	<b>15</b> 15° <b>25</b> 25° <b>38</b> 38° <b>45</b> 45° <b>60</b> 60°	<b>27</b> 2700K <b>30</b> 3000K <b>40</b> 4000K	<b>B</b> black <b>W</b> white	<b>W</b> wall mounted



+61 (03) 9790 8999  
lighting@verbatim.com.au  
www.verbatimlighting.com.au



information is subject to change without prior notice. images are for illustrative purposes only

# hellion large wall

stena series



introducing the hellion wall IP65 wall mounted range. featuring a contemporary design, this luminaire is perfect for a variety of outdoor applications such as illuminating walkways, building exteriors, and parking areas. with its various optics and wattages it is possible to easily customise the lighting to fit specific needs.

with its high-quality die-cast aluminium construction and integral driver, the hellion wall is the perfect choice to enhance outdoor areas.

## specifications

system wattage: 30W, 45W, 56W, 2x20W or 2x30W

luminaire output: 2400lm (30W)

4350lm (45W)

6000lm (56W)

2 x 1350lm (2x20W)

2 x 2000lm (2x30W)

CCT: 2700K, 3000K, 4000K

optics: 24°, 36°, 60°

CRI: >80

control: non-dim

operating voltage: 240Vac

finish: white & black

housing: aluminium

diffuser: safety tempered glass


enclosure protection: IP65

operating temp: 25°C

lifetime: 50,000hrs

warranty: 5 years

accessories: N/A



## product code

product group	group designation	wattage	dimmable	optics	cct	fixture colour	mounting
FS	HL	30	Do	24	27	B	W
stena	hellion large	30W	non-dim	24°	2700K	black	wall mounted
		45		36	30	W	
		45W		36°	3000K	white	
		56		60	40		
		56W		60°	4000K		
		220					
		2x20W					
		230					
		2x30W					



+61 (03) 9790 8999  
lighting@verbatim.com.au  
www.verbatimlighting.com.au



information is subject to change without prior notice. images are for illustrative purposes only

# cortile



## wall led luminaire



the cortile wall light is designed to blend into commercial buildings with a smooth flat surface finished in a warm matte grey powder coat. the individual optics over each LED deliver an asymmetric spread of light, illuminating public spaces sufficiently for safety and security. with its high lumen output of 125lm/w this affordable IP65 wall light is perfect for schools and other community buildings.

### specifications

system wattage:	20W
luminaire output:	2500lm
CCT:	3000K, 4000K
optics:	90° asymmetric
CRI:	ra70
control:	non-dim
operating voltage:	240Vac
finish:	grey
housing:	die-cast aluminum
diffuser:	polycarbonate optical lens
enclosure protection:	IP65, IK08
operating temp:	-20°C to +40°C
lifetime:	50,000hrs
warranty:	5 years



### product code

product group	wattage	dimnable	beam angle	cct	fixture colour	mounting
<b>FC</b> cortile	<b>20</b> 20W	<b>Do</b> non-dim	<b>90</b> 90° asymmetric	<b>30</b> 3000K <b>40</b> 4000K	<b>G</b> grey	<b>W</b> wall



+61 (03) 9790 8999  
lighting@verbatim.com.au  
www.verbatimlighting.com.au



information is subject to change without prior notice. images are for illustrative purposes only

# mighty bollard

## rigid series




the mighty bollard series is designed to produce low glare illumination with a range of optics available. the soft curves will enhance any outdoor environment while the concealed fixing plate and rag bolt kit will ensure secure installation.

the mighty 500 delivers 14W while the mighty 900 delivers 24W, encased in a matt black powder coated aluminium body and a clear multi optic PC lens.

### specifications

system wattage:	14W (mighty 500); 24W (mighty 900)
luminaire output:	1190lm up to 1920lm
CCT:	3000K, 4000K
optics:	type 4, type 5
CRI:	80
macadam:	<4
control:	non-dim, DALI or casambi
operating voltage:	240V AC; 24V DC (optional)
finish:	matte black
housing:	die-cast aluminium
diffuser:	multi-optic PC lens
enclosure protection:	IP66, IK10
operating temp:	-30°C to +50°C
lifetime:	50,000hrs
warranty:	5 years
accessories:	visor



### optics



type 4



type 5

### product code

product group	group designation	dimmmable	beam angle	cct	fixture colour	accessories
<b>FR</b> rigid	<b>M5</b> mighty 500 <b>M9</b> mighty 900	<b>Do</b> non-dim <b>DD</b> DALI <b>CS</b> casambi	<b>T4</b> type 4 <b>T5</b> type 5	<b>30</b> 3000K <b>40</b> 4000K <b>50</b> 5000K	<b>B</b> black	<b>V</b> visor



+61 (03) 9790 8999  
lighting@verbatim.com.au  
www.verbatimlighting.com.au



# halo bollard

## rigid series

The Halo bollard is designed to deliver 360 degrees of low glare illumination through an opal inner lens and clear outer lens. The white internal reflector enables indirect illumination making this perfect for public spaces and residential walk ways.

The halo 10 delivers 25W while the halo 5 delivers 14W, encased in a matt black powder coated alu body with an opal inner lens, white reflector and clear outer lens.

Supplied with integral or remote driver. Complete with ragbolt kit for secure installation.

### specifications

system wattage:	14W (halo 5) or 25W (halo 10)
luminaire output:	1400lm up to 3250lm
CCT:	3000K, 4000K
optics:	type 5
CRI:	80
control:	non-dim, DALI or casambi
operating voltage:	240Vac, 24Vdc (optional)
finish:	matte black
housing:	die-cast aluminium
diffuser:	clear or opal lens
enclosure protection:	IK10, IP66
operating temp:	-30°C to +50°C
lifetime:	46,000hrs (L90)
warranty:	5 years
accessories:	clear or opal lens


### optics



type 5

### product code

product group	group designation	dimmmable	optics	cct	fixture colour	accessories
FR rigid	H5 halo 5 H10 halo 10	Do non-dim DD DALI CS Casambi	T5 type V	30 3000K 40 4000K	B black	C clear lens O opal lens



+61 (03) 9790 8999  
lighting@verbatim.com.au  
www.verbatimlighting.com.au

